

MOTUL MOTYLGEAR



Gearbox and rear axle lubricant

SAE 75W-90

Semi Synthetic

TYPE OF USE

Specially recommended for gearboxes hard to shift

All gearboxes and hypoï d rear axles without limited slip system.

All types of cars: Circuit, Group A, Rallye, 4WD...

In gearboxes and rear axles with limited slip system, use MOTUL 90 PA or HYPO BM LS.

In automatic gearboxes, use MOTUL DEXRON IID or MOTUL TRANSMISSION FLUID.

Meets SAE 75W to 90 manufacturers' requirements.

PERFORMANCES

STANDARDS API GL4 and GL5 / MIL-L-2105D

Very high lubricating power which decreases friction and wear.

Very high fluidity under low temperatures which allows easier gear changing.

Thermal stability under high temperature.

Extreme pressure, Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE	75W-90
Density at 15°C (59°F)	ASTM D1298	0.883
Viscosity at 40°C (104°F)	ASTM D445	81 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.5 mm ² /s
Viscosity index	ASTM D2270	188
Flash point	ASTM D92	200°C / 392°F
Pour point	ASTM D97	-48°C / -54°F

